


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: G07D 13/00	A1	(11) International Publication Number: WO 99/67750 (43) International Publication Date: 29 December 1999 (29.12.99)
(21) International Application Number: PCT/SE99/01023 (22) International Filing Date: 10 June 1999 (10.06.99) (30) Priority Data: 9802096-9 12 June 1998 (12.06.98) SE (71) Applicant (for all designated States except US): NYBOHOV DEVELOPMENT AB [SE/SE]; P.O. Box 47041, S-100 74 Stockholm (SE). (72) Inventor; and (75) Inventor/Applicant (for US only): LUNDBLAD, Leif [SE/SE]; Djurgårdssläätten 100, S-115 21 Stockholm (SE). (74) Agents: NILSSON, Karl et al.; Stenhagen Patentbyrå AB, P.O. Box 4630, S-116 91 Stockholm (SE).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>In English translation (filed in Swedish).</i>

(54) Title: BANKNOTE HANDLING MACHINE**(57) Abstract**

A banknote handling machine having an infeed part (1) for receiving externally posted banknotes and including detector means (11) for checking the genuineness, quality and value of posted banknotes. The detector means (11) functions to sort false banknotes and banknotes of poor quality from remaining banknotes. A processor unit (12) controls transportation of poor quality banknotes along a transport part (13) to a unit (16-18) for storing and packaging said banknotes, and the transportation of at least part of the remaining, genuine and accepted banknotes to a unit (14-17-18) for storing and packaging these banknotes in accordance with their denomination. An outfeed part (2) enables banknotes ordered externally via a banknote ordering means (25) to be dispensed from storage means (21). A processor unit controls the transportation of genuine and accepted banknotes primarily to the storage means (21) in the outfeed part (2) and only secondarily to storage means (14) in the infeed part (1).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

BANKNOTE HANDLING MACHINE**FIELD OF INVENTION**

5 The present invention relates to a banknote handling machine,
and more specifically to a machine that includes an infeed
part for receiving banknotes that are posted from outside the
machine and including detector means for checking the whether
the banknotes are genuine or not, and the quality and
10 denomination of said banknotes.

In a further development of the invention, the banknote
handling machine also includes an outfeed part for dispensing
banknotes from a banknote storage means in response to an
15 order given through the medium of an externally located
banknote ordering means.

BACKGROUND PRIOR ART

20 Dual-purpose automatic apparatus for dispensing and
depositing banknotes are known to the art; c.f. U.S. Patent
Specification 4,447,714 in this respect. It is also known to
provide detection means for checking deposited banknotes;
c.f. European Patent Specification 0.213.094 in this respect.
25 These and similar automatic apparatus have been found to
function reasonably well in practice, although they have
their limitations with respect to greater freedom in the flow
of banknotes, i.e. as opposed to shutting off excessively
large volumes of banknotes in one and the same place (costs
30 interest), the ability to replenish an automatic cash
dispenser or automatic telling machine with banknotes during
the daytime without opening the security box, and enhanced

security with respect to the transportation of any surplus banknotes from one place to another place where a banknote deficiency exists.

5 The object of the present invention is to provide banknote handling machines that fulfil these requirements and desiderata and which generally simplify and make less expensive the flow of banknotes in the community, for instance by reducing the need of quality sorting, banknote
10 authenticity checks and the need to count said banknotes prior to destruction (the National Central Bank). Another advantage is that banknotes handled through the novel machine can be circulated in the community without needing to be re-counted when a bundle of banknotes in a disposable cassette
15 changes owner.

SUMMARY OF THE INVENTION

The inventive banknote handling machine includes an infeed
20 part for receiving externally posted banknotes. For the purpose of checking the genuineness and denominational value of posted banknotes the machine includes detector means for sorting false banknotes and banknotes of poor quality from other (accepted) banknotes. A processor unit controls the
25 transport of banknotes of poor quality through the machine, along a transport path to a banknote packaging unit in which these banknotes are stored in a cassette means.

In a further development of the invention, the banknote
30 handling machine also includes a an outfeed part for dispensing banknotes from storage devices in response to an order entered externally through the medium of banknote

ordering means. The processor unit controls the transportation of genuine and accepted banknotes directly to storage means in the dispenser part of the machine and only secondarily to storage means in the infeed part of said machine. Alternatively, the processor unit transports banknotes from storage means in the infeed part of the machine to storage means in the outfeed or dispensing part of said machine on the basis of the number of banknotes contained in this latter storage means.

These and other characteristic features of the invention will be apparent from the accompanying Claims.

DESCRIPTION OF PREFERRED EMBODIMENTS

The invention will now be described in more detail with reference to the accompanying drawing which illustrates schematically a banknote handling machine constructed in accordance with the invention.

The inventive banknote handling machine includes a banknote infeed part 1 and a banknote outfeed part 2.

The infeed part 1 includes a banknote depositing compartment 10, detector means 11, processing unit 12, transport path 13'-13"-13, first storage means 14, second storage means 15, first stacking means 16, second stacking means 17, and a banknote packaging unit 18.

A deposit is made by placing banknotes, e.g. a bundle of banknotes, possibly of mutually different denominations, in the infeed compartment 10, which can accommodate up to 500

banknotes. These banknotes are separated one by one and passed along an upper transport path 13', past the detector means 11 and up to guide means (direction changing means) 13", which leads the banknotes down to a lower transport path 13.

The detector means 11 is positioned close to the infeed compartment 10 and is designed to separate false banknotes, banknotes of poor quality and other banknotes. By separating is meant here a sorting process in which banknotes that pass the detecting means are "marked" in some appropriate way that will enable said banknotes to be handled as "false", "poor" or "accepted" banknotes during their subsequent transportation.

The storage means 14, similar to several other similar storage means in the machine, includes two belts between which banknotes are stored, a winding-up drum 141, and two unwinding drums 142 and 143. The leading edge of a banknote arriving at the storage means actuates a sensor 144 which, in response, starts-up three motors each of which functions to drive a respective drum 141-143. The banknote is drawn about 120 mm in between the belts, which are wound-up together on the winding-up drum 141, where there is sufficient space to accommodate about 500 banknotes. As the belts are wound onto the drum, banknote information is sent to the processor unit 12, so that an account can be kept of the sequence between the banknotes. Banknotes are taken from the storage means 14, by delivering to the motors impulses that cause the drums to rotate in an opposite direction.

A manipulator 19 is provided along the transport path close to the storage means 14, 15, for correcting the positions of those banknotes which may have been twisted or displaced laterally during transportation.

5

Each of the stacking means 16, 17 includes a stacker wheel which gathers mutually sequential banknotes in a storage compartment into a bundle. When the bundle contains an given number of banknotes, the bundle is clamped by a pair of arms and fed down to the so-called cassetting or packaging unit 18.

10

The cassetting or packaging unit 18 includes two reels of packaging material (plastic). The bundle of banknotes to be packaged is drawn down into a pocket comprised of two plastic lengths of mutually equal lengths and widths, one from each reel. The plastic lengths are pressed together around the bundle and welded together at their edges with the aid of Teflon® coated hotmelt wire. This known technique is described in more detail in U.S. Patent Specification 5,031,379.

15

20

25

The processor unit 12 controls transportation of banknotes of poor quality along the transport part 13 to units 16-18 for storing and packaging these banknotes. This unit is comprised of the stacker means 16 and the packaging unit 18.

30

The manner in which the processor unit 12 controls banknotes along different parts of the transport 13 to different destinations with the aid of path selectors, detectors and so on, is part of conventional technology and will not therefore be described in detail here.

In one further development of the invention, the banknote handling machine includes a banknote dispensing part 2 of given design for dispensing banknotes ordered externally to the outfeed opening or dispenser opening 27 from storage means 21 via an order implementing means 25 (thus not from the processor unit 12). The processor unit 12 controls the transportation of genuine and accepted banknotes fed into the infeed part 1 primarily to the storage means 21 in the outfeed part 2 and only to storage means 14 or 15 in the infeed part 1 when the storage means in the outfeed part is full.

When necessary, the processor unit 12 controls transportation of banknotes from the storage means 14 in the infeed part 1 banknotes present in said storage means.

The outfeed part 2 includes a number of storage means, namely the means 21, 22, 23, 24, each of which is intended to store banknotes of the same denomination, for instance the means 21 and 22 are intended to store banknotes of 100 SEK and the means 23 and 24 are intended to store banknotes of 500 SEK, depending on the demand that can be expected in view of past experience.

So-called small-change cash, i.e. banknotes of smaller denominational value, such as one-hundred notes of 20 SEK and fifty notes of 50 SEK, can be ordered either through the order means 25 for withdrawal in the outfeed opening 27 in the dispenser part 2, or via an outer packaging management centre in the infeed part 1 for later collection and distribution by a transport company. This facility also includes the possibility of ordering the delivery of

banknotes from the storage means in the outfeed or dispensing part to the infeed part for storage and possible packaging therein. This enables the outfeed part of the machine to be emptied completely of banknotes if so desired.

5

False banknotes detected in the detector means 11 may either be returned directly via the transport part 13' to an outfeed compartment close to the deposit compartment 10, or transported to, e.g., the stacking means 16 and from there to the packaging unit 18 where they are packaged together with an automatically printed receipt containing the number of banknotes, the date, etc., and information concerning the person who deposited the banknotes, e.g. through his/her account number. If so desired, the source of false banknotes can be looked for, which should have a certain preventative effect.

10

15

20

25

30

Generally speaking, the major part of the banknotes fed into the infeed part 1 and then accepted will be transported directly to the outfeed part 2, whereas surplus accepted banknotes will be stored in the infeed part 1 for later packaging in the packaging unit 18 in disposable cassettes if desired, these cassettes being collected in a space 26 beneath the packaging unit. The disposable cassettes will preferably accommodate one-hundred bundles of banknotes together with a receipt, the text of which is printed conveniently on the inner surface of the package or cassette immediately before commencing the packaging operation. This organisation of the mechanical function of the machine will greatly increase the capacity of the machine and result in much greater flexibility and more economic handling of banknotes than earlier known banknote handling apparatus.

Sorting of banknotes with respect to quality and with respect to banknotes that must be destroyed, simplifies machine handling and facilitates the work associated with the destruction of banknotes outside the machine (carried out under the management of the National Central Bank).

According to one further development of the invention, the machine is provided with a destruction unit in which banknotes are shredded or torn to pieces so as to render them useless. Destruction of the banknotes can be effected inside the machine under safe electronic control steered by the processor unit. The detector means may also be designed to read the numbers carried by the banknotes, so as to obtain continuously information as to which banknotes have been destroyed and the total value of these banknotes on each occasion.

The significant possibilities afforded by the novel machine in de-centralising banknote handling procedures will be evident from the following summary.

A plurality of machines can be controlled over parts of a country or over the whole of the country, by a Co-operative centre and via an electronic network, for instance Internet. Banks, stores, shops and other bodies that require money report this requirement to the Co-operative centre, which is in constant contact with security vehicles that geographically circulate within the area as necessary. The Co-operative centre is in receipt of statistics that show the requirement of banknotes and the flow of money concerned and are therefore well aware of the money that will be required for each machine. Ordered emptying of surplus banknotes by

packaging can therefore be effected from the infeed and outfeed part (module) of respective machines. When necessary, the outfeed part of a machine can be filled with banknotes from its infeed part, where banknotes are stored, or

5 alternatively externally when it is necessary to open the machine. Disposable cassettes containing banknotes and collected from machines are delivered to those machines that have asked for banknotes and are located in a bank or in a shop or store, or in an automatic banknote dispensing

10 machine. Because the banknotes are delivered in closed and sealed disposable cassettes, counting of loose banknotes is obviated.

CLAIMS


1. A banknote handling machine having an infeed part (1) for receiving externally posted banknotes and comprising
5 detector means (11) for controlling the genuineness, quality and denominational value of the posted banknotes, characterised in that the detector means (11) is designed to sort-out false banknotes, banknotes of poor quality and other banknotes; and in that the machine includes a processor unit
10 (12) which is designed to control the transportation of poor quality banknotes along a transport path (13) to a banknote storing and packaging unit (16-18), and to control transportation of at least a part of the remaining, genuine and accepted banknotes to a unit (14-17-18) for storing and
15 packaging said banknotes in accordance with their value.

2. A banknote handling machine according to Claim 1, comprising an outfeed part (2) for dispensing from storage means (21) banknotes ordered externally via a banknote order
20 means (25), characterised in that the processor unit (12) is designed to control transportation of banknotes from storage means (14) in the infeed part (1) to storage means (21) in the outfeed part (2) in accordance with the number of banknotes that are contained in the last mentioned storage
25 means (21).

3. A banknote handling machine according to Claim 2, characterised in that the processor unit (12) is designed to control transportation of genuine and accepted banknotes
30 primarily to the storage means (21) in the outfeed part (2) and secondarily to the storage means (14) in the infeed part (1).

4. A banknote handling machine according to Claim 1,
characterised in that the infeed part (1) includes at least
two banknote storage means (14, 15), two banknote collecting
and stacking means (16, 17), and a banknote packaging means
5 (18); and in that the processor unit (12) is designed to
control transportation of poor quality banknotes from the
detector means (12) directly to one (16) of said banknote
stacking means and from there to the packaging means (18),
and to control transportation of at least part of the
10 remaining, accepted banknotes to one (14) of said storage
means and from there to the remaining banknote stacking means
(17) and banknote packaging means (18).

Fig. 1



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/01023

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: G07D 13/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: G07D, G07F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0024704 A1 (OMRON TATEISI ELECTRONIC CO.), 11 March 1981 (11.03.81), page 38, line 14 - line 18 --	1-4
Y	US 4639582 A (ARIKAWA ET AL), 27 January 1987 (27.01.87), details 22,23 --	1-4
Y	US 5468941 A (SASAKI), 21 November 1995 (21.11.95), section 2 --	1-4
P,Y	EP 0871149 A1 (NCR INTERNATIONAL INC.), 14 October 1998 (14.10.98) -- -----	1-4

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

6 Sept 1999

14-10-1999

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Gunilla Jonsson
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

02/08/99

International application No.

PCT/SE 99/01023

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0024704 A1	11/03/81	SE 0024704 T3	
		JP 1623303 C	25/10/91
		JP 2008341 B	23/02/90
		JP 56033757 A	04/04/81
		US 4365700 A	28/12/82
<hr/>			
US 4639582 A	27/01/87	DE 3517848 A,C	21/11/85
		GB 2159500 A,B	04/12/85
		GB 2194777 A,B	16/03/88
		JP 1651093 C	30/03/92
		JP 3012355 B	20/02/91
		JP 60241189 A	30/11/85
		JP 1651094 C	30/03/92
		JP 3012356 B	20/02/91
		JP 60241190 A	30/11/85
<hr/>			
US 5468941 A	21/11/95	JP 7037138 A	07/02/95
<hr/>			
EP 0871149 A1	14/10/98	GB 9707243 D	00/00/00
		JP 10289349 A	27/10/98
<hr/>			